



16

HARMONIZE STANDARD : TS EN 1469
PRODUCTS : NATURAL STONE PRODUCTS FOR CLADDING
PETROGRAPHIC DESCRIPTION : TRAVERTINE
PLACE OF USE : INDOOR - OUTDOOR
PRODUCT NAME : NOCHE TRAVERTINE

COMPANY
NAME /
ADDRESS

LUXMAR MADENCİLİK SANAYİ VE TİCARET LİMİTED ŞİRKETİ
Hızırbey mahallesi 111.cadde No: 109/111
Merkez, Isparta / TURKEY

Web : www.luxmarstone.com

E-mail : info@luxmarstone.com

CHARACTERISTICS	DECLARATION	TEST METHOD
FIRE RESISTANCE	CLASS A1	WITHOUT TEST (96/603/EC)
FLEXURAL STRENGTH Mpa	10,07	TS EN 13161
FROST RESISTANCE Mpa	78	TS EN 12371
APPARENT DENSITY kg/m ³	2400	TS EN 1936
OPEN POROSITY %	3,09	TS EN 1936
ABRASION STRENGTH mm	NPD	TS EN 14157
WATER ABSORPTION BY CAPILLARY OF WEIGHT g/m ² .s ^{0,5}	1,86	TS EN 1925
WATER ABSORPTION AT ATMOSPHERIC PRESSURE BY WEIGHT	1,4	TS EN 13755